

ICB-62M2713MAA

SKU: 230801



Abb. ähnlich

1/2.8" Network Camera, 1920x1080, Day/Night, DOL-WDR, 2.7-13.5mm, Infrared, IP67

Main Features

1/2.8" Sony STARVIS CMOS Sensor
Excellent light sensitivity
Resolution max. 1920x1080 (Full HD)
Motorised varifocal lens 2.7~13.5mm
DOL-WDR (120dB) by triple scan images at 30/25fps
Motion Detection, Privacy Zones, Slow Shutter

Browser independent (IE, Edge, Safari, Firefox, Chrome)
Smart Codec H.265 ROI (Region of Interest)
Supports ONVIF Profile S and Profile T
Vertical View 90°/270° Modus, H-Flip, Mirror
Power supply PoE, IP67
Integrated connection box including connection board

Specifications

| | |
|-------------------------|--|
| Dimensions (HxWxD) | 130,50x82,15x265,80mm |
| Series | eneo AN-Series, eneo Candid Small |
| Resolution Standard | HD 1080p |
| System | True Day&Night |
| Sensor size | 1/2.8" |
| Imager | CMOS |
| Video compression | H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG |
| Image resolution max. | 1920x1080 |
| Image Transmission Rate | 30 fps |
| Day&Night switch | ICR |

ICB-62M2713MAA

Continuation of the specifications

| | |
|-------------------------------|--|
| Sensitivity | 0,0008 Lux at F1,6, 40 IRE |
| Digital Noise Reduction | yes |
| Lens Type | Varifocal (motorized) |
| Focal Length | 2,7 - 13,5 mm |
| Iris Control | DC |
| Zoom Factor | 4x |
| Digital Zoom | yes |
| Observe (62 px/m) | 16,6 - 80,5 m |
| Recognize (125 px/m) | 8,2 - 40,1 m |
| Identify (250 px/m) | 3,9 - 20,1 m |
| Detect (25px/m) | 44 - 198 m |
| Horizontal Angle of View | 108 - 32° |
| Vertical Angle of View | 56 - 18° |
| MOD (Minimum Object Distance) | 0,5 m |
| Illumination | Infrared |
| Housing | Outdoor |
| Color (housing) | Pantone Cool Gray 1C |
| Housing material | Aluminium |
| Blower | yes |
| Video outputs | no |
| Alarm inputs | 1 |
| Alarm outputs | 1 |
| Audio support | no |
| Ethernet interface | 100Base-TX, 10Base-T |
| Serial interfaces | Ethernet |
| Internal storage | microSDHC card, microSDXC card |
| Analysis functions | Motion detection, Tampering Detection (TD) |
| Mounting | Ceiling mount, Wall mount |
| Supply voltage | PoE |
| Power consumption | 8W, PoE |
| Power over Ethernet | IEEE 802.3af |
| Vandal proof | no |
| Operating temperature | -50°C ~ +50°C |
| ONVIF | ONVIF Profile S, ONVIF Profile T |
| Protection rating | IP67 |
| Low Speed Shutter | yes |
| Backlight Compensation | BLC, HLC |
| Wide Dynamic Range (WDR) | D-WDR |
| Motion Detector | yes |
| Camera type | Bullet |
| Remote configuration | Browser |

ICB-62M2713MAA

Continuation of the specifications

| | |
|---------------------------|-------------|
| Illumination range | approx. 40m |
| Weight | 1.25kg |
| Manufacturer order number | 230801 |

Optional Accessory

| SKU | Name | Description |
|--------|-------------------|---|
| 218218 | eneo Site Manager | Management Software for eneo IP products |
| 202641 | PM-42A | Pole mount adaptor for eneo Candid, Candid S, Candid M, WB1, AK-5, AK-4 |

Optional Services

| SKU | Name | Description |
|--------|----------------------------|---|
| 211123 | LACKIERUNG Bulletkamera | Extra charge for special paint bullet camera in RAL color |
| 214441 | LACKIERUNG Grundkosten | Painting basic costs once per RAL color and delivery lot |
| 229234 | Vorkonfiguration IP-Kamera | Preconfiguration 1x IP camera Function test, FW update |

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

