

ICB-62M0550MAA

SKU: 231833



Abb. ähnlich

1/2.8" Network Camera, 1920x1080, Day/Night, DOL-WDR, 5.0-50mm, Infrared, IP67

Main Features

1/2.8" Sony STARVIS CMOS Sensor
Excellent light sensitivity
Resolution max. 1920x1080 (Full HD)
Motorised varifocal lens 5.0~50mm
DOL-WDR (120dB) by triple scan images at 30/25fps
Motion Detection, Privacy Zones, Slow Shutter

Browser independent (IE, Edge, Safari, Firefox, Chrome)
Smart Codec H.265 ROI (Region of Interest)
Supports ONVIF Profile S and Profile T
Vertical View 90°/270° Modus, H-Flip, Mirror
Power supply PoE, IP67
Integrated connection box including connection board

Specifications

Dimensions (HxWxD)	130,50x82,15x265,80mm
Series	eneo AN-Series, eneo Candid Small
Resolution Standard	HD 1080p
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG
Image resolution max.	1920x1080
Image Transmission Rate	30 fps
Day&Night switch	ICR

ICB-62M0550MAA

Continuation of the specifications

Sensitivity	0,001 Lux at F1,6, 40 IRE
Digital Noise Reduction	yes
Lens Type	Varifocal (motorized)
Focal Length	5 - 50 mm
Iris Control	DC
Zoom Factor	10x
Digital Zoom	yes
Observe (62 px/m)	30,3 - 298,2 m
Recognize (125 px/m)	15,2 - 147,6 m
Identify (250 px/m)	7,5 - 74 m
Detect (25px/m)	76,4 - 740,4 m
Horizontal Angle of View	49,9 - 8°
Vertical Angle of View	26,7 - 4,5°
MOD (Minimum Object Distance)	0,5 m
Illumination	Infrared
Housing	Outdoor
Color (housing)	Pantone Cool Gray 1C
Housing material	Aluminium
Blower	yes
Video outputs	no
Alarm inputs	1
Alarm outputs	1
Audio support	no
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	microSDHC card, microSDXC card
Analysis functions	Motion detection, Tampering Detection (TD)
Mounting	Ceiling mount, Wall mount
Supply voltage	PoE
Power consumption	9W, PoE
Power over Ethernet	IEEE 802.3af
Vandal proof	no
Operating temperature	-50°C ~ +50°C
ONVIF	ONVIF Profile S, ONVIF Profile T
Protection rating	IP67
Low Speed Shutter	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	D-WDR
Motion Detector	yes
Camera type	Bullet
Remote configuration	Browser

ICB-62M0550MAA

Continuation of the specifications

Illumination range	approx. 40m
Weight	1.3kg
Manufacturer order number	231833

Optional Accessory

SKU	Name	Description
218218	eneo Site Manager	Management Software for eneo IP products
202641	PM-42A	Pole mount adaptor for eneo Candid, Candid S, Candid M, WB1, AK-5, AK-4

Optional Services

SKU	Name	Description
211123	LACKIERUNG Bulletkamera	Extra charge for special paint bullet camera in RAL color
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

