

IPB-62M2713MAA

SKU: 232571



Abb. ähnlich

1/2.8" Network Camera, 1920x1080, Day/Night, DOL-WDR, 2.7-13.5mm, Infrared, IP66

Main Features

1/2.8" Sony STARVIS CMOS Sensor
Excellent light sensitivity
Resolution max. 1920x1080 (Full HD)
Motorised varifocal lens 2.7~13.5mm
DOL-WDR (120dB) by triple scan images at 30/25fps
Motion Detection, Privacy Zones, Slow Shutter

Browser independent (IE, Edge, Safari, Firefox, Chrome)
Smart Codec H.265 ROI (Region of Interest)
Supports ONVIF Profile S and Profile T
Vertical View 90°/270° Modus, H-Flip, Mirror
Bullet Housing (metal), IP66
Power supply PoE or 12VDC

Specifications

Dimensions (HxWxD)	78,5x78,5x214mm
Series	eneo AN-Series
Resolution Standard	HD 1080p
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG
Image resolution max.	1920x1080
Image Transmission Rate	30 fps
Day&Night switch	ICR

IPB-62M2713MAA

Continuation of the specifications

Sensitivity	0,0008 Lux at F1,6, 40 IRE
Digital Noise Reduction	yes
Lens Type	Varifocal (motorized)
Focal Length	2,7 - 13,5 mm
Iris Control	DC
Zoom Factor	4x
Digital Zoom	yes
Observe (62 px/m)	16,6 - 80,5 m
Recognize (125 px/m)	8,2 - 40,1 m
Identify (250 px/m)	3,9 - 20,1 m
Detect (25px/m)	44 - 198 m
Horizontal Angle of View	108 - 32°
Vertical Angle of View	56 - 18°
MOD (Minimum Object Distance)	0,5 m
Illumination	Infrared
Housing	Outdoor
Color (housing)	Pantone Cool Gray 1C
Housing material	Aluminium
Blower	yes
Video outputs	no
Alarm inputs	nein
Alarm outputs	no
Audio support	no
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	no
Analysis functions	Motion detection, Tampering Detection (TD)
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC, PoE
Power consumption	12VDC, 8W, 8W, PoE
Power over Ethernet	IEEE 802.3af
Vandal proof	no
Operating temperature	-20°C ~ +50°C
ONVIF	ONVIF Profile S, ONVIF Profile T
Protection rating	IP66
Low Speed Shutter	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	D-WDR
Motion Detector	yes
Camera type	Bullet
Remote configuration	Browser

IPB-62M2713MAA

Continuation of the specifications

Illumination range	approx. 40m
Weight	600g
Manufacturer order number	232571

Optional Accessory

SKU	Name	Description
230863	AK-10	Camera junction box for wall and ceiling mounting
218218	eneo Site Manager	Management Software for eneo IP products

Optional Services

SKU	Name	Description
211123	LACKIERUNG Bulletkamera	Extra charge for special paint bullet camera in RAL color
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

