



# MPD-62V2713P0A

SKU: 233014



1/2,8" HD Dome, Fix, Day&Night 1920x1080, Lens 2,7-13,5mm, IR LED, 12VDC, Indoor

## Main Features

- ..... 1/2.8" 2.3 Megapixel progressive scan CMOS sensor
- ..... Compact plastic housing for indoor use
- ..... Resolution max. 1920x1080 (Full HD)
- ..... Multisignal: HD-TVI, AHD, CVI, Composite selectable
- ..... Variofocal 2.8~12mm day&night lens
- ..... LSC (Lens shading compensation)

- ..... Removable infrared cut filter
- ..... 3D-DNR noise reduction
- ..... Digital Wide Dynamic Range (D-WDR)
- ..... Integral motion detection
- ..... Wedge adapter included (10° inclination)
- ..... Scratch resistant hard coated bubble

## Specifications

Dimensions (HxWxD)	100x116mm
Serial interfaces protocols	UTC (HD-Signal Format)
Series	eneo KX-Series
Resolution Pixels	1920x1080, 960x576
Resolution Pixels	1920x1080, 960x576
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Day&Night switch	ICR
Sensitivity	0,3 Lux at F1,3, 40 IRE

# MPD-62V2713P0A

## Continuation of the specifications

Digital Noise Reduction	yes
Lens Type	Varifocal
Focal Length	2,7 - 13,5 mm
Iris Control	DC
Zoom Factor	4x
Digital Zoom	no
Observe (62 px/m)	16,6 - 80,5 m
Recognize (125 px/m)	8,2 - 40,1 m
Identify (250 px/m)	3,9 - 20,1 m
Detect (25px/m)	44 - 198 m
Horizontal Angle of View	95 - 27°
Vertical Angle of View	49 - 15°
MOD (Minimum Object Distance)	0,5 m
Illumination	Infrared
Housing	Indoor
Color (housing)	white
Color (bubble)	clear
Housing material	Plastic
Heater	no
Video outputs	AHD, Composite (CVBS), CVI, HD-TVI
Alarm inputs	nein
Alarm outputs	no
Serial interfaces	Coaxitron (HD Protocol)
Analysis functions	Defog
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC
Power consumption	6W
Vandal proof	no
Operating temperature	-10°C ~ +50°C
Low Speed Shutter	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	D-WDR
Motion Detector	yes
Signal format	AHD @ 2MP, Composite (FBAS), CVI @ 2MP, HD-TVI @ 2MP
Camera type	Dome
Frame rate	25/30fps @ 1920x1080p
Aperture range (F)	F1,3
Illumination range	approx. 30m
Weight	260g
Manufacturer order number	233014

# MPD-62V2713P0A

## Optional Accessory

SKU	Name	Description
225085	MAM-5DC1004M0A	Distributor, 1x BNC Input HD-TVI, CVI, AHD, CVBS, 4x BNC Output
220299	MAM-5MM1001M0A	Converter, HD-CVI, HD-TVI, AHD, Composite to HDMI, VGA, Composite, Indoor
212984	TVA-1201TRA	UTP Transmitter+Receiver, UTP, BNC, 250m, Indoor, HD TVI CVI, AHD, CVBS, Active, 12V
212985	TVA-1201TRP	UTP Transmitter+Receiver, UTP, BNC, 150m, Indoor, HD TVI CVI, AHD, CVBS, Passive

## Optional Services

SKU	Name	Description
211125	LACKIERUNG Fix-Dome-Kamera	Extra charge for special paint fixed dome in RAL color
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
229233	Vorkonfiguration analoge Kamera	Preconfiguration 1x analog camera Function test, FW update

## Your contact person

VIDEOR E. Hartig GmbH  
 Carl-Zeiss-Straße 8  
 63322 Rödermark  
 Germany

