



MED-62V2713M0A

SKU: 233015



1/2,8" HD Dome, Fix, Day&Night 1920x1080, Lens 2,7-13,5mm, IR LED, 12VDC, IP66

Main Features

1/2.8" 2.3 Megapixel progressive scan CMOS sensor

Compact metal housing for outdoor use

Resolution max. 1920x1080 (Full HD)

Multisignal: HD-TVI, AHD, CVI, Composite selectable

Variofocal 2.8~12mm day&night lens

LSC (Lens shading compensation)

Removable infrared cut filter

RS-485 control in-output

3D-DNR noise reduction

Integral motion detection

Scratch resistant hard coated bubble

Easy installation, 3-Axis gimbal

Specifications

Dimensions (HxWxD)	108x144,4mm
Serial interfaces protocols	UTC (HD-Signal Format)
Series	eneo KX-Series
Resolution Pixels	1920x1080, 960x576
Resolution Pixels	1920x1080, 960x576
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Day&Night switch	ICR
Sensitivity	0,3 Lux at F1,3, 40 IRE

MED-62V2713M0A

Continuation of the specifications

Digital Noise Reduction	yes
Lens Type	Varifocal
Focal Length	2,7 - 13,5 mm
Iris Control	DC
Zoom Factor	4x
Digital Zoom	no
Observe (62 px/m)	16,6 - 80,5 m
Recognize (125 px/m)	8,2 - 40,1 m
Identify (250 px/m)	3,9 - 20,1 m
Detect (25px/m)	44 - 198 m
Horizontal Angle of View	95 - 27°
Vertical Angle of View	49 - 15°
MOD (Minimum Object Distance)	0,5 m
Illumination	Infrared
Housing	Outdoor
Color (housing)	Pantone Cool Gray 1C
Color (bubble)	clear
Housing material	Aluminium
Heater	no
Blower	no
Video outputs	AHD, Composite (CVBS), CVI, HD-TVI
Alarm inputs	nein
Alarm outputs	no
Serial interfaces	Coaxitron (HD Protocol)
Analysis functions	Defog
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC
Power consumption	6W
Vandal proof	yes
Operating temperature	-20°C ~ +50°C
Certifications	IK10
Protection rating	IP66
Low Speed Shutter	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	D-WDR
Motion Detector	yes
Signal format	AHD @ 2MP, Composite (FBAS), CVI @ 2MP, HD-TVI @ 2MP
Camera type	Dome
Frame rate	25/30fps @ 1920x1080p
Aperture range (F)	F1,3
Illumination range	approx. 30m

MED-62V2713M0A

Continuation of the specifications

Weight	1.0kg
Manufacturer order number	233015

Optional Accessory

SKU	Name	Description
230864	AK-11	Camera junction box for wall and ceiling mounting
215644	DOME-WB3	Wall bracket for eneo Dome Cameras MED-62xxxxM0A and IED-62xxxxM0A
225085	MAM-5DC1004M0A	Distributor, 1x BNC Input HD-TVI, CVI, AHD, CVBS, 4x BNC Output
220299	MAM-5MM1001M0A	Converter, HD-CVI, HD-TVI, AHD, Composite to HDMI, VGA, Composite, Indoor
218653	PS12DC-11	Plug-in Power Supply Unit, 100-240VAC/12VDC (1,0A), regulated, with DC Plug
212984	TVA-1201TRA	UTP Transmitter+Receiver, UTP, BNC, 250m, Indoor, HD TVI CVI, AHD, CVBS, Active, 12V
212985	TVA-1201TRP	UTP Transmitter+Receiver, UTP, BNC, 150m, Indoor, HD TVI CVI, AHD, CVBS, Passive

Optional Services

SKU	Name	Description
211125	LACKIERUNG Fix-Dome-Kamera	Extra charge for special paint fixed dome in RAL color
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
229233	Vorkonfiguration analoge Kamera	Preconfiguration 1x analog camera Function test, FW update

MED-62V2713M0A

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

