

MPC-52A0030M0A

SKU: 233052



1/3" HD Camera, 1920x1080, 30x AF Zoom
4,3-129mm, T-WDR, HD-SDI, EX-SDI, TVI,
Composite

Main Features

1/3" 2,0 Megapixel Panasonic CMOS-Sensor
Resolution max. 1920x1080, 1080p@60/50fps
Optical 30x Auto Focus Zoom, 4,3~129mm
Multisignal Output HD-SDI, EX-SDI, TVI, Composite
Real time True WDR
Digital Noise Reduction(2D+3D)

Digital Image Stabilization
Privacy Masking, Defog
Slow Speed Shutter
Compact Housing
Power Supply 12VDC

Specifications

Dimensions (HxWxD)	74x67x121,5mm
Serial interfaces protocols	Pelco P Pelco D UTC (HD-Signal Format)
Resolution Pixels	1280x720, 1920x1080
Resolution Pixels	1280x720, 1920x1080
Horizontal resolution	700 TVL
System	True Day&Night
Sensor size	1/3"
Imager	CMOS
Day&Night switch	ICR
Sensitivity	0,5 Lux at F1,6, 50 IRE

MPC-52A0030M0A

Continuation of the specifications

Digital Noise Reduction	yes
Lens Type	auto focus zoom
Focal Length	4,3 - 129 mm
Iris Control	DC
Zoom Factor	30x
Digital Zoom	yes
Observe (62 px/m)	28,1 - 842,7 m
Recognize (125 px/m)	13,6 - 411,5 m
Identify (250 px/m)	6,6 - 208 m
Detect (25px/m)	71,2 - 2061,3 m
Horizontal Angle of View	58,9 - 2,11°
Vertical Angle of View	45,3 - 1,61°
MOD (Minimum Object Distance)	0,1 m
Illumination	no
Housing	Indoor
Color (housing)	black, silbermetallic
Housing material	Aluminium
Video outputs	Composite (CVBS), EX-SDI, HD-SDI, HD-TVI
Alarm outputs	1
Serial interfaces	Coaxitron (HD Protocol), RS-485
Analysis functions	Motion detection
Supply voltage	12VDC
Power consumption	6W
Vandal proof	no
Operating temperature	-10°C ~ +50°C
Low Speed Shutter	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	WDR 120dB
Motion Detector	yes
Signal format	Composite (FBAS), EX-SDI (270 Mbps), HD-SDI (1.485 Gbps), HD-TVI @ 2MP
Camera type	Zoom Camera
Frame rate	25/30fps @ 1280x720p, 25/30fps @ 1920x1080p, 50/60fps @ 1280x720p, 50/60fps @ 1920x1080p
Aperture range (F)	F1.6~F4,7
Weight	610g
Manufacturer order number	233052

Optional Accessory

SKU	Name	Description
-----	------	-------------

MPC-52A0030M0A

Continuation of accessory

225085	MAM-5DC1004M0A	Distributor, 1x BNC Input HD-TVI, CVI, AHD, CVBS, 4x BNC Output
220299	MAM-5MM1001M0A	Converter, HD-CVI, HD-TVI, AHD, Composite to HDMI, VGA, Composite, Indoor
212984	TVA-1201TRA	UTP Transmitter+Receiver, UTP, BNC, 250m, Indoor, HD TVI CVI, AHD, CVBS, Active, 12V
212985	TVA-1201TRP	UTP Transmitter+Receiver, UTP, BNC, 150m, Indoor, HD TVI CVI, AHD, CVBS, Passive
219504	WD-30	Wall Mount Bracket with Ball Joint, 1/4" Camera Fixing Screw, Pantone Cool Grey 1C

Optional Services

SKU	Name	Description
211123	LACKIERUNG Bulletkamera	Extra charge for special paint bullet camera in RAL color
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
229233	Vorkonfiguration analoge Kamera	Preconfiguration 1x analog camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

