



# MED-65M2812M0A

SKU: 233706

EAN: 4260229840337



1/2,8" HD Dome, Fix, Day&Night, 2592x1944, Infrared 2,7-13,5mm, 12VDC, IP67

## Main Features

1/2.8" CMOS Image Sensor

Resolution max. 2592x1944

multi-signal: HD-TVI, AHD, CVI, CVBS

2,7-13,5 mm lens with variable focal length (motorized)

Day/night switching (ICR)

2D+3D DNR (Digital Noise Reduction)

Automatic exposure control (1/30s~1/50,000s)

Lens shading correction

IR LED illumination integrated

For outdoor use degree of protection IP67

12VDC power supply, NDAA compliant

## Specifications

EAN/GTIN	4260229840337
Dimensions (HxWxD)	148.0x109.0mm
Series	eneo COAXIZE, eneo IN-Series
Resolution Pixels	1920x1080, 2560x1440, 2592x1944, 960x540
Resolution Pixels	1920x1080, 2560x1440, 2592x1944, 960x540
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Day&Night switch	ICR
Sensitivity	0,05 Lux at F1,2

# MED-65M2812M0A

## Continuation of the specifications

Digital Noise Reduction	2D-DNR, 3D-DNR
Lens Type	Varifocal (motorized)
Focal Length	2,7 - 13,5 mm
Iris Control	DC
Zoom Factor	4x
Digital Zoom	no
Observe (62 px/m)	24,3 - 104,5 m
Recognize (125 px/m)	11,5 - 52,2 m
Identify (250 px/m)	5,2 - 25,6 m
Detect (25px/m)	62,5 - 260,3 m
Horizontal Angle of View	110,6 - 32,6°
Vertical Angle of View	57,3 - 18,3°
MOD (Minimum Object Distance)	0,8 m
Illumination	Infrared
Housing	Outdoor
Color (housing)	Pantone P 179-1, RAL9003
Housing material	Aluminium
Heater	no
Video outputs	AHD, Composite (CVBS), HD-TVI
Alarm inputs	nein
Alarm outputs	no
Serial interfaces	Coaxitron (HD Protocol)
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC
Power consumption	6.5W
Vandal proof	yes
Operating temperature	-30°C ~ +55°C
Certifications	IK10
Protection rating	IP67
Low Speed Shutter	no
Backlight Compensation	BLC
Wide Dynamic Range (WDR)	WDR 120dB
Motion Detector	no
Signal format	AHD @ 2MP, AHD @ 4MP, AHD @ 5MP, Composite (FBAS), CVI @ 2MP, CVI @ 4MP, HD-TVI @ 2MP, HD-TVI @ 4MP, HD-TVI @ 5MP
Camera type	Dome
Frame rate	20fps @ 2592x1944p, 25/30fps @ 1920x1080p, 25/30fps @ 2560x1440p
Aperture range (F)	F1.8~F3.3
Illumination range	approx. 35m
Weight	875g

# MED-65M2812M0A

Continuation of the specifications

Manufacturer order number	233706
---------------------------	--------

## Optional Accessory

SKU	Name	Description
235339	AK-24	Dual camera connection box for Bullet or Fix Dome IN-Series cameras
235525	AK-25	Camera junction box for ceiling pipe DOME-CH6 and wall bracket DOME-WB6
235526	AK-26	Camera junction box for wall- and ceiling mount Fix dome cameras IN-Serie
239856	IND-FMH2	Ceiling installation adapter with white cover ring for dome cameras IN-Series
236125	MAM-5MM2203M0A	Converter, 4K HD-TVI, HD-CVI, AHD, auf HDMI, Indoor 12VDC
235340	WB-24	Wall bracket for Dual camera connection box AK-24

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

