



# IND-42M2808M0A

SKU: 233796



Mini Network Dome Fix, 1920x1080, Day/Night, WDR, AI 2,8-8mm, IR, 12VDC, PoE, IP66

## Main Features

- 1/2.8" Sony STARVIS CMOS sensor, 2 MP/60fps
- AI analysis functions including object classification
- WDR 120dB, 3D-DNR Noise Reduction
- Motorized varifocal lens 2.8-8mm
- Smart Codec H.265/H.264, multi-streaming
- Browser independent (IE, Edge, Safari, Firefox, Chrome)

- Supports ONVIF Profile S and Profile T
- Multilingual menu navigation (OSD)
- Local storage via Micro SD card
- Supports audio and external alarm input and output
- NDA compliance
- IR LED illumination, IP66 and vandal proof IK10

## Specifications

Dimensions (HxWxD)	115x91,6mm
Series	eneo IN-Series
Camera Type	Face recognition, License plate recognition, People Count, Retail Intelligence
Resolution Standard	HD 1080p
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG
Image resolution max.	1920x1080

# IND-42M2808M0A

Continuation of the specifications

Image Transmission Rate	60 fps
Day&Night switch	ICR
Sensitivity	0,002 Lux at F1,2
Digital Noise Reduction	yes
Lens Type	Varifocal (motorized)
Focal Length	2,8 - 8 mm
Iris Control	DC
Zoom Factor	2,8x
Digital Zoom	yes
Observe (62 px/m)	17,8 - 30,3 m
Recognize (125 px/m)	8,4 - 23,7 m
Identify (250 px/m)	4,1 - 11,7 m
Detect (25px/m)	45,7 - 119,5 m
Horizontal Angle of View	107 - 45°
Vertical Angle of View	55 - 26°
MOD (Minimum Object Distance)	0,8 m
Illumination	Infrared
Housing	Outdoor
Color (housing)	Pantone P 179-1, RAL9003
Color (bubble)	clear
Housing material	Aluminium
Heater	no
Blower	no
Rotation range	350°
Video outputs	no
Alarm inputs	1
Alarm outputs	1
Audio support	yes
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	microSD-Kartenslot
Analysis functions	Attribute Detection (AD), Cross Counting (CC), Crowd Density Detection (CD), Face Attendance (FA), Face Detection (FD), Face Recognition (FR), Heat Map (HM), Human&Vehicle Detection (PD&VD), License Plate Detection (LPD), License Plate Recognition (LPR), Line Crossing Detection (LCD), Perimeter Intrusion Detection (PID), Queue Length Detection (QD), Rare Sound Detection (RSD), Stationary Object Detection (SOD)
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC, PoE
Power consumption	7W

# IND-42M2808M0A

Continuation of the specifications

Power over Ethernet	IEEE 802.3af
Vandal proof	yes
Operating temperature	-35°C ~ +60°C, @ Humidity 90% or less (non-condensing)
ONVIF	ONVIF Profile G, ONVIF Profile S, ONVIF Profile T
Certifications	IK10
Protection rating	IP66
Low Speed Shutter	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	D-WDR
Motion Detector	yes
Camera type	Dome
Audio	1/1 Line input and output, 2 Way Audio
Remote configuration	Browser
Illumination range	approx. 20m
Weight	480g
Manufacturer order number	233796

## Optional Accessory

SKU	Name	Description
234753	AK-22	Kamera Anschlussbox für Mini Dome IND-42M2808M0A Wand- oder Deckenmontage
234754	AK-23	Camera connection box for Mini Dome IND-42M2808M0A for holder Dome-WB6/Dome-CH6
235339	AK-24	Dual camera connection box for Bullet or Fix Dome IN-Series cameras
234756	DOME-CH6	Ceiling pipe for junction box AK-23 and AK-25, Length approx. 294mm
234755	DOME-WB6	Wall bracket for Connection box AK-23 and AK-25
234757	DOME-WB7	Wall bracket for Mini Dome IND-42M2808M0A
236198	eneo INsight Installation Tool	Supports adjustments for cameras with AI features for IN-series
234990	eneo INsight mobile	Mobile App for recorder IN- and MN-series
218218	eneo Site Manager	Management Software for eneo IP products
235340	WB-24	Wall bracket for Dual camera connection box AK-24

## Optional Services

SKU	Name	Description
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

# IND-42M2808M0A

Continuation of services

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

