

INP-75A0033MIA

SKU: 234751

EAN: 4260229840160



Netzwerk Dome, PTZ, 33x 2952x1944, Tag/Nacht, WDR, AI Alarm, Audio, 24/12V, PoE, IP66

Main Features

1/2.7" CMOS sensor, maximum resolution 5 MP/30fps

AI analysis functions including object classification

WDR 120dB, 3D-DNR Noise Reduction

Motorized autofocus zoom lens 33x 4.3-142mm

Smart Codec H.265/H.264, multi-streaming

Browser independent (IE, Edge, Safari, Firefox, Chrome)

Supports ONVIF Profile S and Profile T

Local storage via Micro SD card

Audio input and output

IR LED illumination, IP66

NDAA compliance

Wall bracket included

Specifications

EAN/GTIN	4260229840160
Dimensions (HxWxD)	206,4x351,8mm
Series	eneo IN-Series
Camera Type	Face recognition, People Count, Retail Intelligence
Resolution Standard	5 Megapixel
System	True Day&Night
Sensor size	1/2.7"
Imager	CMOS
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG

INP-75A0033MIA

Continuation of the specifications

Image resolution max.	2592x1944
Image Transmission Rate	30 fps
Day&Night switch	ICR
Sensitivity	0,003 Lux at F1,6
Digital Noise Reduction	yes
Lens Type	auto focus zoom
Focal Length	4,3 - 142 mm
Iris Control	DC
Zoom Factor	33x
Observe (62 px/m)	35,6 - 1107,3 m
Recognize (125 px/m)	17 - 548,3 m
Identify (250 px/m)	7,5 - 273,3 m
Detect (25px/m)	90,2 - 2728,4 m
Horizontal Angle of View	55 - 2,3°
Vertical Angle of View	41,6 - 1,7°
Illumination	Infrared
Housing	Outdoor
Color (housing)	black, Pantone P 179-1, RAL9003
Hosuing material	Aluminium
Heater	no
Blower	no
Rotation range	360°
Speed (manual)	200°/Sek.
Speed (preset)	200°/Sek.
Alarm inputs	nein
Alarm outputs	no
Audio support	yes
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	microSD-Kartenslot
Analysis functions	Cross Counting (CC), Face Detection (FD), Face Recognition (FR), Heat Map (HM), Human&Vehicle Detection (PD&VD), Line Crossing Detection (LCD), Perimeter Intrusion Detection (PID), Stationary Object Detection (SOD), Tampering Detection (TD)
Mounting	Wall mount
Supply voltage	12VDC, PoE+
Power consumption	25,5W
Power over Ethernet	IEEE 802.3at
Vandal proof	no
Operating temperature	-30°C ~ +60°C, @ Humidity 90% or less (non-condensing)

INP-75A0033MIA

Continuation of the specifications

ONVIF	ONVIF Profile G, ONVIF Profile S, ONVIF Profile T
Protection rating	IP66
Low Speed Shutter	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	WDR 120dB
Motion Detector	yes
Camera type	PTZ
Audio	1/1 Line input and output, 2 Way Audio
Remote configuration	Browser
Illumination range	approx. 150m
Weight	3.7kg
Manufacturer order number	234751

Optional Accessory

SKU	Name	Description
235562	CM-22	Corner mounting adapter for wall bracket WB-24 and PTZ dome camera INP-75A0033MIA
236198	eneo INsight Installation Tool	Supports adjustments for cameras with AI features for IN-series
234990	eneo INsight mobile	Mobile App for recorder IN- and MN-series
218218	eneo Site Manager	Management Software for eneo IP products
239837	KBD-3NET	Network keyboard with joystick, supports ONVIF protocol, RJ45, 12VDC
235257	PM-21	Pole mounting adapter for camera connection box AK-20 and AK-21

Optional Services

SKU	Name	Description
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

INP-75A0033MIA

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

