



IND-68M2713M0A

SKU: 235254

EAN: 4260229840030



Network Dome Fix, 3840x2160, Day/Night, WDR, AI 2,7-13,5mm, IR, 12VDC, IP67

Main Features

1/2.8" Sony STARVIS CMOS sensor,8 MP/30fps

AI analysis functions including object classification

WDR 120dB, 3D-DNR Noise Reduction

Motorized varifocal lens 2.7-13.5mm

Smart Codec H.265/H.264, multi-streaming

Browser independent (IE, Edge, Safari, Firefox, Chrome)

Supports ONVIF Profile S and Profile T

Multilingual menu navigation (OSD)

Local storage via Micro SD card

Supports audio and external alarm input and output

NDAA compliance

IR LED illumination, IP67 and vandal proof IK10

Specifications

| | |
|---------------------|--|
| EAN/GTIN | 4260229840030 |
| Dimensions (HxWxD) | 109x148,7mm |
| Series | eneo IN-Series |
| Camera Type | Face recognition, License plate recognition, People Count, Retail Intelligence |
| Resolution Standard | 8 Megapixel |
| System | True Day&Night |
| Sensor size | 1/2.8" |
| Imager | CMOS |
| Video compression | H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG |

IND-68M2713M0A

Continuation of the specifications

| | |
|-------------------------------|---|
| Image resolution max. | 3840x2160 |
| Image Transmission Rate | 30 fps |
| Day&Night switch | ICR |
| Sensitivity | 0,009 Lux at F1,6 |
| Digital Noise Reduction | yes |
| Lens Type | Varifocal (motorized) |
| Focal Length | 2,7 - 13,5 mm |
| Iris Control | DC |
| Zoom Factor | 4x |
| Digital Zoom | yes |
| Observe (62 px/m) | 35,4 - 162,4 m |
| Recognize (125 px/m) | 17,2 - 80,3 m |
| Identify (250 px/m) | 8,2 - 40,2 m |
| Detect (25px/m) | 89,9 - 400,6 m |
| Horizontal Angle of View | 111 - 33° |
| Vertical Angle of View | 57 - 18° |
| MOD (Minimum Object Distance) | 0,3 m |
| Illumination | Infrared |
| Housing | Outdoor |
| Color (housing) | Pantone P 179-1, RAL9003 |
| Color (bubble) | clear |
| Housing material | Aluminium |
| Heater | no |
| Blower | no |
| Rotation range | 350° |
| Alarm inputs | 1 |
| Alarm outputs | 1 |
| Audio support | yes |
| Ethernet interface | 100Base-TX, 10Base-T |
| Serial interfaces | Ethernet |
| Internal storage | microSD-Kartenslot |
| Analysis functions | Attribute Detection (AD), Cross Counting (CC), Crowd Density Detection (CD), Face Attendance (FA), Face Detection (FD), Face Recognition (FR), Heat Map (HM), Human&Vehicle Detection (PD&VD), License Plate Detection (LPD), License Plate Recognition (LPR), Line Crossing Detection (LCD), Perimeter Intrusion Detection (PID), Queue Length Detection (QD), Rare Sound Detection (RSD), Stationary Object Detection (SOD) |
| Mounting | Ceiling mount, Wall mount |
| Supply voltage | 12VDC, PoE |
| Power consumption | 8W |

IND-68M2713M0A

Continuation of the specifications

| | |
|---------------------------|--|
| Power over Ethernet | IEEE 802.3af |
| Vandal proof | yes |
| Operating temperature | -35°C ~ +55°C, @ Humidity 90% or less (non-condensing) |
| ONVIF | ONVIF Profile G, ONVIF Profile S, ONVIF Profile T |
| Certifications | IK10 |
| Protection rating | IP67 |
| Low Speed Shutter | yes |
| Backlight Compensation | BLC, HLC |
| Wide Dynamic Range (WDR) | WDR 120dB |
| Motion Detector | yes |
| Camera type | Dome |
| Audio | 1/1 Line input and output, 2 Way Audio |
| Remote configuration | Browser |
| Illumination range | approx. 30m |
| Weight | 950g |
| Manufacturer order number | 235254 |

Optional Accessory

| SKU | Name | Description |
|--------|--------------------------------|---|
| 235339 | AK-24 | Dual camera connection box for Bullet or Fix Dome IN-Series cameras |
| 235525 | AK-25 | Camera junction box for ceiling pipe DOME-CH6 and wall bracket DOME-WB6 |
| 235526 | AK-26 | Camera junction box for wall- and ceiling mount Fix dome cameras IN-Serie |
| 236663 | DOME-WB8 | Wall bracket for PTZ dome INP-54M2812M0A and IND-5 Dome Series |
| 236198 | eneo INsight Installation Tool | Supports adjustments for cameras with AI features for IN-series |
| 234990 | eneo INsight mobile | Mobile App for recorder IN- and MN-series |
| 218218 | eneo Site Manager | Management Software for eneo IP products |
| 237253 | IN-Dome-S2 | Sunshield for eneo IN-series Fix Dome IND-62xx, IND-65xx, IND-68xx |
| 239856 | IND-FMH2 | Ceiling installation adapter with white cover ring for dome cameras IN-Series |
| 239837 | KBD-3NET | Network keyboard with joystick, supports ONVIF protocol, RJ45, 12VDC |
| 235340 | WB-24 | Wall bracket for Dual camera connection box AK-24 |

Optional Services

IND-68M2713M0A

| SKU | Name | Description |
|-----|------|-------------|
|-----|------|-------------|

IND-68M2713M0A

Continuation of services

| | | |
|--------|----------------------------|--|
| 229234 | Vorkonfiguration IP-Kamera | Preconfiguration 1x IP camera Function test, FW update |
|--------|----------------------------|--|

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

