



IAM-5SG1008MMC

SKU: 236275



Gigabit Switch, Managed, 360W, 4x PoE++, 4x poE+, 1000Mbps, Industrial Design, -40°C~+75°C

Main Features

Gigabit PoE Switch, DIN Rail, Fanless

8x Gigabit PoE ports (4x PoE++90W, 4x PoE+30W)

Supports IEEE 802.3af/at/bt

Supports P-PoE Permanent PoE technology

Total max. 360W (optional power supply)

4x SFP Gigabit Uplink Ports thereof 2x 10G SFP+

L2 management, web configuration, web management

Supports VLAN, RTSP, "Fast Ring" and QoS

Fast Ring redundancy, reconfiguration <20ms

Redundant power supply possible

Error relay, console port, status LEDs

Temperature range -40°C~+75°C

Specifications

Manufacturer order number	236275
---------------------------	--------

Optional Accessory

SKU	Name	Description
218218	eneo Site Manager	Management Software for eneo IP products
216479	SFP-0850M10	SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
218758	SFP-0850M40	SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C

IAM-5SG1008MMC

Continuation of accessory

216478	SFP-1310M40	SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C
216566	SFP-1310S10	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C
216477	SFP-1310S40	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector -40°~+75°C

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

