



# INB-75M0550M0A

SKU: 236661

EAN: 4260229840504



Network Camera Bullet, 2592x1944, Day/Night, WDR, AI, 5,0-50mm, IR, 12VDC, PoE, IP67

## Main Features

- 1/2.7" Omnivision CMOS sensor,
- Maximum resolution 2592x1944 pixels, 30fps
- AI analysis functions including object classification
- WDR 120dB, 3D-DNR noise reduction
- Motorised varifocal lens 5.0-50mm
- Smart Codec H.265/H.264, multi-streaming

- Browser independent (Edge, Safari, Firefox, Chrome)
- Supports ONVIF profiles S/T/G
- Local storage via Micro SD card
- Supports audio and external alarm input and output
- NDA compliance
- IR LED illumination, IP67

## Specifications

|                     |  |
|---------------------|--|
| EAN/GTIN            | 4260229840504  |
| Dimensions (HxWxD)  | 89.95x96.70x301.11mm   |
| Series              | eneo IN-Series   |
| Camera Type         | Face recognition, License plate recognition, People Count, Retail Intelligence |
| Resolution Standard | 5 Megapixel  |
| System              | True Day&Night   |
| Sensor size         | 1/2.7"   |
| Imager              | CMOS   |
| Video compression   | H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG             |

# INB-75M0550M0A

Continuation of the specifications

|                               |   |
|-------------------------------|---|
| Image resolution max.         | 2592x1944   |
| Image Transmission Rate       | 30 fps  |
| Day&Night switch              | ICR   |
| Sensitivity                   | 0,003 Lux at F1,6   |
| Digital Noise Reduction       | yes   |
| Lens Type                     | Varifocal (motorized)   |
| Focal Length                  | 5 - 50 mm   |
| Iris Control                  | DC  |
| Zoom Factor                   | 10x   |
| Digital Zoom                  | yes   |
| Observe (62 px/m)             | 41 - 385 m  |
| Recognize (125 px/m)          | 20,1 - 193,2 m  |
| Identify (250 px/m)           | 9,6 - 97 m  |
| Detect (25px/m)               | 102,4 - 964 m   |
| Horizontal Angle of View      | 45 - 7°   |
| Vertical Angle of View        | 33 - 5°   |
| MOD (Minimum Object Distance) | 0,2 m   |
| Illumination                  | Infrared  |
| Housing                       | Outdoor   |
| Color (housing)               | Pantone P 179-1, RAL9003  |
| Housing material              | Aluminium   |
| Heater                        | no  |
| Blower                        | no  |
| Video outputs                 | no  |
| Alarm inputs                  | 1   |
| Alarm outputs                 | 1   |
| Audio support                 | yes   |
| Ethernet interface            | 100Base-TX, 10Base-T  |
| Serial interfaces             | Ethernet  |
| Internal storage              | microSD-Kartenslot  |
| Analysis functions            | Attribute Detection (AD), Cross Counting (CC), Crowd Density Detection (CD), Face Attendance (FA), Face Detection (FD), Face Recognition (FR), Heat Map (HM), Human&Vehicle Detection (PD&VD), License Plate Detection (LPD), License Plate Recognition (LPR), Line Crossing Detection (LCD), Perimeter Intrusion Detection (PID), Queue Length Detection (QD), Rare Sound Detection (RSD), Stationary Object Detection (SOD) |
| Mounting                      | Ceiling mount, Wall mount   |
| Supply voltage                | 12VDC, PoE  |
| Power consumption             | 12W   |
| Power over Ethernet           | IEEE 802.3af  |

# INB-75M0550M0A

Continuation of the specifications

|                           |  |
|---------------------------|--|
| Vandal proof              | no   |
| Operating temperature     | -35°C ~ +60°C, @ Humidity 90% or less (non-condensing) |
| ONVIF                     | ONVIF Profile G, ONVIF Profile S, ONVIF Profile T      |
| Protection rating         | IP67   |
| Low Speed Shutter         | yes  |
| Backlight Compensation    | BLC, HLC   |
| Wide Dynamic Range (WDR)  | WDR 120dB  |
| Motion Detector           | yes  |
| Camera type               | Bullet   |
| Audio                     | 1/1 Line input and output, 2 Way Audio                 |
| Remote configuration      | Browser  |
| Illumination range        | approx. 80m  |
| Manufacturer order number | 236661   |

## Optional Accessory

| SKU    | Name                           | Description   |
|--------|--------------------------------|---|
| 233754 | AK-20                          | Camera connection box for Wall and ceiling mounting, IN Series Bullet Cameras |
| 233775 | AK-21                          | Camera connection box for Wall and ceiling mounting, IN Series Bullet Cameras |
| 235339 | AK-24                          | Dual camera connection box for Bullet or Fix Dome IN-Series cameras           |
| 236198 | eneo INsight Installation Tool | Supports adjustments for cameras with AI features for IN-series               |
| 234990 | eneo INsight mobile            | Mobile App for recorder IN- and MN-series                                     |
| 218218 | eneo Site Manager              | Management Software for eneo IP products                                      |
| 239837 | KBD-3NET                       | Network keyboard with joystick, supports ONVIF protocol, RJ45, 12VDC          |
| 235257 | PM-21                          | Pole mounting adapter for camera connection box AK-20 and AK-21               |
| 235340 | WB-24                          | Wall bracket for Dual camera connection box AK-24                             |

## Optional Services

| SKU    | Name                       | Description  |
|--------|----------------------------|--|
| 229234 | Vorkonfiguration IP-Kamera | Preconfiguration 1x IP camera Function test, FW update |

# INB-75M0550M0A

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

