



INB-78M0550M0A

SKU: 236662

EAN: 4260229840498



Network Camera Bullet, 3840x2160, Day/Night, WDR, AI 5,0-50mm, IR, 12VDC, PoE, IP67

Main Features

- 1/2.8" Sony STARVIS CMOS sensor,
- Maximum resolution 3840x2160 pixels, 30fps
- AI analysis functions including object classification
- WDR 120dB, 3D-DNR noise reduction
- Motorised varifocal lens 5.0-50mm
- Smart Codec H.265/H.264, multi-streaming

- Browser independent (Edge, Safari, Firefox, Chrome)
- Supports ONVIF profiles S/T/G
- Local storage via Micro SD card
- Supports audio and external alarm input and output
- NDA compliance
- IR LED illumination, IP67

Specifications

EAN/GTIN	4260229840498
Dimensions (HxWxD)	89.95x96.70x301.11mm
Series	eneo IN-Series
Camera Type	Face recognition, License plate recognition, People Count, Retail Intelligence
Resolution Standard	8 Megapixel
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG

INB-78M0550M0A

Continuation of the specifications

Image resolution max.	3840x2160
Image Transmission Rate	30 fps
Day&Night switch	ICR
Sensitivity	0,009 Lux at F1,6
Digital Noise Reduction	yes
Lens Type	Varifocal (motorized)
Focal Length	5 - 50 mm
Iris Control	DC
Zoom Factor	10x
Digital Zoom	yes
Observe (62 px/m)	61,5 - 597 m
Recognize (125 px/m)	29,9 - 295 m
Identify (250 px/m)	15,1 - 147,8 m
Detect (25px/m)	153,6 - 1484 m
Horizontal Angle of View	49 - 7°
Vertical Angle of View	27 - 4°
MOD (Minimum Object Distance)	0,2 m
Illumination	Infrared
Housing	Outdoor
Color (housing)	Pantone P 179-1, RAL9003
Housing material	Aluminium
Heater	no
Blower	no
Video outputs	no
Alarm inputs	1
Alarm outputs	1
Audio support	yes
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	microSD-Kartenslot
Analysis functions	Attribute Detection (AD), Cross Counting (CC), Crowd Density Detection (CD), Face Attendance (FA), Face Detection (FD), Face Recognition (FR), Heat Map (HM), Human&Vehicle Detection (PD&VD), License Plate Detection (LPD), License Plate Recognition (LPR), Line Crossing Detection (LCD), Perimeter Intrusion Detection (PID), Queue Length Detection (QD), Rare Sound Detection (RSD), Stationary Object Detection (SOD)
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC, PoE
Power consumption	13W
Power over Ethernet	IEEE 802.3af

INB-78M0550M0A

Continuation of the specifications

Vandal proof	no
Operating temperature	-35°C ~ +60°C, @ Humidity 90% or less (non-condensing)
ONVIF	ONVIF Profile G, ONVIF Profile S, ONVIF Profile T
Protection rating	IP67
Low Speed Shutter	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	WDR 120dB
Motion Detector	yes
Camera type	Bullet
Audio	1/1 Line input and output, 2 Way Audio
Remote configuration	Browser
Illumination range	approx. 80m
Manufacturer order number	236662

Optional Accessory

SKU	Name	Description
233754	AK-20	Camera connection box for Wall and ceiling mounting, IN Series Bullet Cameras
233775	AK-21	Camera connection box for Wall and ceiling mounting, IN Series Bullet Cameras
235339	AK-24	Dual camera connection box for Bullet or Fix Dome IN-Series cameras
236198	eneo INsight Installation Tool	Supports adjustments for cameras with AI features for IN-series
234990	eneo INsight mobile	Mobile App for recorder IN- and MN-series
218218	eneo Site Manager	Management Software for eneo IP products
239837	KBD-3NET	Network keyboard with joystick, supports ONVIF protocol, RJ45, 12VDC
235257	PM-21	Pole mounting adapter for camera connection box AK-20 and AK-21
235340	WB-24	Wall bracket for Dual camera connection box AK-24

Optional Services

SKU	Name	Description
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

INB-78M0550M0A

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

