

SC-MUCP0801E

SKU: 236774



1-channel UTP-Transmitter, Receiver, supports AHD, TVI, CVI and CVBS

Main Features

1CH 'Video + Power + RS-485 Data' transmission via CAT.5e	Power supply for one camera (~8W/ DC12V)
Supports various signals: AHD/TVI/CVI (~1080p), CVBS (NTSC/PAL)	SD-IP2.0 reduction of video noise
Video In: ~ 1080p25/30 (AHD, TVI, CVI, CVBS)	Built-in overvoltage protection circuit
Video Out: ~ 1080p25/30 (AHD, TVI, CVI, CVBS)	Power supply 12VDC, 48VDC
Max. 700m over CAT.5e (AHD, CVBS)	-10°C ~ +50°C Temperature range
Max. 400m (CVI), Max. 300m (TVI) via CAT.5e	-10°C ~ +50°C Temperaturbereich

Specifications

Type	Media Converter
Series	SeeEyes SC-IP
Transmission medium	UTP
Ports	1
Model	mini module
Type of unit	transmitter / receiver
Range	400 m
Signal transmission	audio, video
Operating temperature	-10°C ~ +50°C
Operation mode	active

SC-MUCP0801E

Continuation of the specifications

Manufacturer order number

SC-MUCP0801E

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

