



IAD-5SG1004MUC

SKU: 237369



Gigabit Switch, Unmanaged, 60W, 4x PoE, 1x RJ45, 1x SFP, 10/100/1000 Mbps, Desktop

Abb. ähnlich

Main Features

Gigabit PoE switch, desktop application

4x 10/100/1000 PoE+ ports, IEEE 802.3af/at

Gigabit uplink ports: 1x RJ45, 1x SFP

Up to 30W per port, total ≤60W.

Overvoltage protection IEC61000-4-5 (6KV).

Temperature range (operation) -5°C~45°C

CCTV mode enables transmission up to 250m @10Mbps

CCTV mode supports PoE watchdog function

Plug and Play, no settings required

Metal housing

Specifications

Dimensions (HxWxD)	27x135x86mm
Type	Unmanaged
Mounting	desktop
Blower	no
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
VLAN	no
Ports	1x 10/100/1000Base-T, 1x 1000Base-X SFP, 4x 10/100/1000Base-T (PoE)
PoE ports (number)	4
Management	no
Model	Desktop
Supply voltage	48~57 VDC

IAD-5SG1004MUC

Continuation of the specifications

Power consumption	65W
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
PoE budget	60 W
Operating temperature	-5°C ~ +45°C
Weight	300g
Manufacturer order number	237369

Optional Accessory

SKU	Name	Description
216479	SFP-0850M10	SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
218758	SFP-0850M40	SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C
216478	SFP-1310M40	SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C
216566	SFP-1310S10	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C
216477	SFP-1310S40	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector -40°~+75°C

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

