



IND-58F0028MTLA

SKU: 238647

EAN: 4260229840641



Network Dome Fix, Turret, Low Light, 3840x2160, Day/Night WDR, AI, 2,8mm, 12VDC, PoE, IP67

Main Features

1/1.8" Sony STARVIS CMOS sensor

Very good detail recognition even in dark areas

Maximum resolution 3840x2160 pixels, 30fps

AI analysis functions including object classification

WDR 120dB, 3D DNR noise reduction

Lens fixed focal length 2.8mm

Smart codec H.265/H.264, multi-streaming

Browser-independent (Edge, Safari, Firefox, Chrome)

Supports ONVIF profiles S/T/G

Local storage via micro SD card

NDA compliance

White light LED illumination, IP67

Specifications

EAN/GTIN	4260229840641
Dimensions (HxWxD)	97,9x115,5mm
Series	eneo IN-Series
Camera Type	Face recognition, License plate recognition, People Count, Retail Intelligence
Resolution Standard	8 Megapixel
System	24h color
Sensor size	1/1.8"
Imager	CMOS
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG

IND-58F0028MTLA

Continuation of the specifications

Image resolution max.	3640x2160
Image Transmission Rate	30 fps
Day&Night switch	no
Sensitivity	0.0005 Lux @ F1,0
Digital Noise Reduction	yes
Lens Type	fixed focal length
Focal Length	2,8 mm
Iris Control	DC
Digital Zoom	yes
Horizontal Angle of View	112°
Vertical Angle of View	61°
MOD (Minimum Object Distance)	0,7 m
Illumination	White light
Housing	Outdoor
Color (housing)	Pantone P 179-1, RAL9003
Housing material	Aluminium
Heater	no
Blower	no
Video outputs	no
Alarm inputs	nein
Alarm outputs	no
Audio support	yes
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	microSD-Kartenslot
Analysis functions	Attribute Detection (AD), Cross Counting (CC), Crowd Density Detection (CD), Face Attendance (FA), Face Detection (FD), Face Recognition (FR), Heat Map (HM), Human&Vehicle Detection (PD&VD), License Plate Detection (LPD), License Plate Recognition (LPR), Line Crossing Detection (LCD), Perimeter Intrusion Detection (PID), Queue Length Detection (QD), Rare Sound Detection (RSD), Stationary Object Detection (SOD)
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC, PoE
Power consumption	12VDC: max. 5,1W , PoE: max. 6,5W
Power over Ethernet	IEEE 802.3af
Vandal proof	no
Operating temperature	-30°C ~ +55°C, @ Humidity 95% or less (non-condensing)
ONVIF	ONVIF Profile G, ONVIF Profile S, ONVIF Profile T
Protection rating	IP67

IND-58F0028MTLA

Continuation of the specifications

Low Speed Shutter	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	WDR 120dB
Motion Detector	yes
Camera type	Dome
Audio	2 Way Audio, built-in loudspeaker, built-in microphone
Remote configuration	Browser
Illumination range	approx. 25m
Weight	575g
Manufacturer order number	238647

Optional Accessory

SKU	Name	Description
233775	AK-21	Camera connection box for Wall and ceiling mounting, IN Series Bullet Cameras
234757	DOME-WB7	Wall bracket for Mini Dome IND-42M2808M0A
236198	eneo INsight Installation Tool	Supports adjustments for cameras with AI features for IN-series
218218	eneo Site Manager	Management Software for eneo IP products

Optional Services

SKU	Name	Description
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

