

# ExCam miniTube IP T08-VA1.2.K1.BOR-N.H-005.N-P

SKU: 240902



Network camera in stainless steel housing in accordance with RL 2014/34/EU (ATEX) and IECEx, 1080p, 4x optical zoom, IP68

Rack accessories are not included

## Main Features

CMOS sensor 1/2.8" with FullHD 1920x1080p

Motorized varifocal lens with 4x optical zoom

Day/night functionality

Stainless steel AISI 316L

Certified for hazardous areas according to ATEX, IECEx, INMETEC

Protection class IP66/68 (IEC 60529)

Multi-streaming and video compression H.265

Made in Germany

## Specifications

Series	ExCam
Camera Type	Explosionssgeschützt
Resolution Standard	HD 1080p
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG
Image resolution max.	1920x1080
Image Transmission Rate	30 fps
Day&Night switch	ICR
Sensitivity	0,0008 Lux bei 40 IRE F1.6
Low Speed Shutter	yes

# ExCam miniTube IP T08-VA1.2.K1.BOR-N.H-005.N-P

Continuation of the specifications

Digital Noise Reduction	yes
Backlight Compensation	n/a
Wide Dynamic Range (WDR)	120dB
Motion Detector	yes
Lens Type	Varifocal (motorized)
Focal Length	2,7 - 13,5 mm
Digital Zoom	yes
Horizontal Angle of View	80 - 32°
Illumination	no
Housing	Outdoor
Color (housing)	Edelstahl
Hosuing material	Stainless steel
Heater	no
Video outputs	no
Alarm inputs	nein
Audio support	no
Serial interfaces	Ethernet
Internal storage	no
Supply voltage	PoE
Power over Ethernet	IEEE 802.3af
Operating temperature	-30°C ~ +50°C
ONVIF	ONVIF Profile S, ONVIF Profile T
Certifications	ATEX, EACex, IECEX, INMETRO, MASC, PESO, UKEX
Protection rating	IP66/68
Manufacturer order number	22070526

## Optional Accessory

SKU	Name	Description
240936	ExConnection Rail T04.5-D.BOR-4PoE++-100Base	High-performance PoE switch for the Ex area IP66-base-resistant encapsulated housing with sight glass, Explosion protection approval 2014/34/EU
240937	ExConnection Rail T04.6-D.BOR-8PoE++-100Base	High-performance PoE switch for the Ex area IP66-base-resistant encapsulated housing with sight glass, Explosion protection approval 2014/34/EU
240934	ExTB-3 Klemmkasten für ExCam Serie	Model: T12-M20-M20-M20
240932	Mastadapter PMB-VA1.x + VA.2.x	Compatible with all WMB wall brackets of the ExCam Series with the model codes T08-VA1.x, T08-VA2x and T03
240912	SKD02-T Kabel Kit 30 m	30 meter SKD02-T system cable Digital special cable with Ex approval according to DIN EN 60079-14

# ExCam miniTube IP T08-VA1.2.K1.BOR-N.H-005.N-P

Continuation of accessory

240913	SKDP03-T Kabel Kit 30 m	30 meter SKDP03-T system cable Digital special cable with Ex approval according to DIN EN 60079-14
240914	Wandausleger WMB-VA0.1 / VA1.2 (Edelstahl)	Compatible with housing sizes VA0.x and VA1.2
240920	Wetterschutzdach WPR-VA1.2 (Edelstahl)	(Stainless Steel)

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

