



ExCam IPM1137-LE-WL T08-VA2.2.K1.BOR-L.H-005.N-P

SKU: 240905



camera in stainless steel housing in accordance with RL 2014/34/EU (ATEX) and IECEx, external EX-WL-illumination, 5MP, i-CS Remote Zoom

Main Features

1/2.7" CMOS sensor with 5 MP (2592 x 1944)	Version with white light
Day/night functionality	Protection class IP66/68 (IEC 60529)
Powerful remote zoom lens (i-CS)	One-cable solution (PoE)
AISI 316L stainless steel	H.265 video compression
Certified for hazardous areas according to ATEX, IECEx, INMETRO, EAC-Ex	
Zone 1/21, gas group IIC, temperature class T5	

Specifications

Series	ExCam
Camera Type	Explosiongeschützt
Resolution Standard	5 Megapixel
System	True Day&Night
Sensor size	1/2.7"
Imager	CMOS
Video compression	H.264, H.265, M-JPEG
Image resolution max.	2592x1944
Image Transmission Rate	30 fps
Day&Night switch	ICR

ExCam IPM1137-LE-WL T08-VA2.2.K1.BOR-L.H-005.N-P

Continuation of the specifications

Sensitivity	0,17 Lux bei 50 IRE F1.4
Digital Noise Reduction	yes
Lens Type	Varifocal
Focal Length	3,5 - 10 mm
Digital Zoom	yes
Horizontal Angle of View	99 - 31°
Illumination	White light
Housing	Explosionssgeschützt
Color (housing)	Edelstahl
Housing material	Stainless steel
Heater	no
Video outputs	no
Alarm inputs	nein
Audio support	no
Serial interfaces	Ethernet
Internal storage	microSD-Kartenslot
Supply voltage	PoE
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
Operating temperature	-30°C ~ +50°C
ONVIF	ONVIF Profile G, ONVIF Profile M, ONVIF Profile S, ONVIF Profile T
Certifications	ATEX, EACex, IECEx, INMETRO, MASC, UKEX
Protection rating	IP66/68
Low Speed Shutter	yes
Backlight Compensation	n/a
Wide Dynamic Range (WDR)	120dB
Motion Detector	yes
Manufacturer order number	22070476

Optional Accessory

SKU	Name	Description
240936	ExConnection Rail T04.5-D.BOR-4PoE++-100Base	High-performance PoE switch for the Ex area Explosion-resistant encapsulated housing with sight glass, Explosion protection approval 2014/34/EU
240937	ExConnection Rail T04.6-D.BOR-8PoE++-100Base	High-performance PoE switch for the Ex area Explosion-resistant encapsulated housing with sight glass, Explosion protection approval 2014/34/EU
240934	ExTB-3 Klemmkasten für ExCam Serie	Model: T12-M20-M20-M20
240932	Mastadapter PMB-VA1.x + VA.2.x	Compatible with all WMB wall brackets of the ExCam Series with the model codes T08-VA1.x, T08-VA2x and T03

ExCam IPM1137-LE-WL T08-VA2.2.K1.BOR-L.H-005.N-P

Continuation of accessory

240912	SKD02-T Kabel Kit 30 m	30 meter SKD02-T system cable Digital special cable with Ex approval according to DIN EN 60079-14
240913	SKDP03-T Kabel Kit 30 m	30 meter SKDP03-T system cable Digital special cable with Ex approval according to DIN EN 60079-14
240916	Wandausleger WMB-VA2.3	
240924	Wetterschutzdach WPR-VA2.2 (Edelstahl)	(Stainless Steel)

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

