

ExCam IPQ1785 T08-VA2.3.K3.BOR2-N.H-005.N-P

SKU: 240907



camera in stainless steel housing in accordance with RL 2014/34/EU (ATEX) and IECEx, 1080p, 32x optical zoom, IP68, -10°C/+60°C

Rack accessories are not included

Main Features

1/2.8" CMOS sensor with 2 MP (1920 x 1080)

Powerful motorized zoom autofocus lens (32x optical)

AISI 316L stainless steel

Certified for hazardous areas according to ATEX, IECEx, INMETRO, ENEC, IMBRO, Ex-Ex

Optional powerful wiper solution with torque control

Lightfinder and WDR

Protection class IP66/68 (IEC 60529)

H.265 video compression

Videokomprimierung H.265

Specifications

| | |
|-------------------------|-------------------------------|
| Series | ExCam |
| Camera Type | Explosionssgeschützt |
| Resolution Standard | HD 1080p |
| System | True Day&Night |
| Sensor size | 1/2.8" |
| Imager | CMOS |
| Video compression | Axis Zipstream, H.264, M-JPEG |
| Image resolution max. | 1920x1080 |
| Image Transmission Rate | 30 fps |
| Day&Night switch | ICR |
| Sensitivity | 0,16 Lux bei 50 IRE F1.4 |
| Digital Noise Reduction | yes |

ExCam IPQ1785 T08-VA2.3.K3.BOR2-N.H-005.N-P

Continuation of the specifications

| | |
|---------------------------|---|
| Lens Type | auto focus zoom |
| Focal Length | 4,3 - 137 mm |
| Digital Zoom | no |
| Horizontal Angle of View | 60 - 2,3° |
| Housing | Explosionsschutz |
| Color (housing) | Edelstahl |
| Housing material | Stainless steel |
| Heater | no |
| Video outputs | no |
| Alarm inputs | nein |
| Audio support | no |
| Serial interfaces | Ethernet |
| Internal storage | microSD-Kartenslot |
| Supply voltage | PoE |
| Power over Ethernet | IEEE 802.3af, IEEE 802.3at |
| Operating temperature | -30°C ~ +60°C |
| ONVIF | ONVIF Profile G, ONVIF Profile S, ONVIF Profile T |
| Certifications | ATEX, EACex, IECEX, INMETRO, MASC, UKEX |
| Protection rating | IP66/68 |
| Low Speed Shutter | yes |
| Backlight Compensation | no |
| Wide Dynamic Range (WDR) | 120dB |
| Motion Detector | yes |
| Manufacturer order number | 22070234 |

Optional Accessory

| SKU | Name | Description |
|--------|--|---|
| 240936 | ExConnection Rail T04.5-D.BOR-4PoE++-100Base | High-performance PoE switch for the Ex area IP66- and IP68-resistant encapsulated housing with sight glass, Explosion protection approval 2014/34/EU |
| 240937 | ExConnection Rail T04.6-D.BOR-8PoE++-100Base | High-performance PoE switch for the Ex area IP66- and IP68-resistant encapsulated housing with sight glass, Explosion protection approval 2014/34/EU |
| 240934 | ExTB-3 Klemmkasten für ExCam Serie | Model: T12-M20-M20-M20 |
| 240932 | Mastadapter PMB-VA1.x + VA.2.x | Compatible with all WMB wall brackets of the ExCam Series with the model codes T08-VA1.x, T08-VA2x and T03 |
| 240912 | SKD02-T Kabel Kit 30 m | 30 meter SKD02-T system cable Digital special cable with Ex approval according to DIN EN 60079-14 |
| 240913 | SKDP03-T Kabel Kit 30 m | 30 meter SKDP03-T system cable Digital special cable with Ex approval according to DIN EN 60079-14 |

ExCam IPQ1785 T08-VA2.3.K3.BOR2-N.H-005.N-P

Continuation of accessory

| | | |
|--------|----------------------------|--|
| 240916 | Wandausleger WMB-VA2.3 | |
| 240926 | Wetterschutzdach WPR-VA2.3 | |

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

