

ExCam IPQ1785 T08-VA2.3.K3.BOR2-N.H-005.N-P

SKU: 240907



camera in stainless steel housing in accordance with RL 2014/34/EU (ATEX) and IECEx, 1080p, 32x optical zoom, IP68, -10°C/+60°C

Rack accessories are not included

Main Features

1/2.8" CMOS sensor with 2 MP (1920 x 1080)	Lightfinder and WDR
Powerful motorized zoom autofocus lens (32x optical)	Protection class IP66/68 (IEC 60529)
AISI 316L stainless steel	H.265 video compression
Certified for hazardous areas according to ATEX, IECEx, INMETRO, ENEC, IMBRO, Ex-Ex	Made in Germany
Optional powerful wiper solution with torque control	Videokomprimierung H.265

Specifications

Series	ExCam
Camera Type	Explosionssgeschützt
Resolution Standard	HD 1080p
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Video compression	Axis Zipstream, H.264, M-JPEG
Image resolution max.	1920x1080
Image Transmission Rate	30 fps
Day&Night switch	ICR
Sensitivity	0,16 Lux bei 50 IRE F1.4
Digital Noise Reduction	yes

ExCam IPQ1785 T08-VA2.3.K3.BOR2-N.H-005.N-P

Continuation of the specifications

Lens Type	auto focus zoom
Focal Length	4,3 - 137 mm
Digital Zoom	no
Horizontal Angle of View	60 - 2,3°
Housing	Explosionssgeschützt
Color (housing)	Edelstahl
Housing material	Stainless steel
Heater	no
Video outputs	no
Alarm inputs	nein
Audio support	no
Serial interfaces	Ethernet
Internal storage	microSD-Kartenslot
Supply voltage	PoE
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
Operating temperature	-30°C ~ +60°C
ONVIF	ONVIF Profile G, ONVIF Profile S, ONVIF Profile T
Certifications	ATEX, EACex, IECEX, INMETRO, MASC, UKEX
Protection rating	IP66/68
Low Speed Shutter	yes
Backlight Compensation	no
Wide Dynamic Range (WDR)	120dB
Motion Detector	yes
Manufacturer order number	22070234

Optional Accessory

SKU	Name	Description
240936	ExConnection Rail T04.5-D.BOR-4PoE++-100Base	High-performance PoE switch for the Ex area IP66- and IP68-resistant encapsulated housing with sight glass, Explosion protection approval 2014/34/EU
240937	ExConnection Rail T04.6-D.BOR-8PoE++-100Base	High-performance PoE switch for the Ex area IP66- and IP68-resistant encapsulated housing with sight glass, Explosion protection approval 2014/34/EU
240934	ExTB-3 Klemmkasten für ExCam Serie	Model: T12-M20-M20-M20
240932	Mastadapter PMB-VA1.x + VA.2.x	Compatible with all WMB wall brackets of the ExCam Series with the model codes T08-VA1.x, T08-VA2x and T03
240912	SKD02-T Kabel Kit 30 m	30 meter SKD02-T system cable Digital special cable with Ex approval according to DIN EN 60079-14
240913	SKDP03-T Kabel Kit 30 m	30 meter SKDP03-T system cable Digital special cable with Ex approval according to DIN EN 60079-14

ExCam IPQ1785 T08-VA2.3.K3.BOR2-N.H-005.N-P

Continuation of accessory

240916	Wandausleger WMB-VA2.3	
240926	Wetterschutzdach WPR-VA2.3	

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

