

ExCam IPQ6075 T08-TNXCD-N.H-005.N-P

SKU: 240909



Network PTZ dome camera in stainless steel housing accordance with RL 2014/34/EU (ATEX) and IECEx, 1080p, 40x optical zoom, 0°C/60°C

Main Features

1/2.8" CMOS sensor with 2 MP (1920 x 1080)

Powerful motorized zoom autofocus lens (40x optical)

AISI 316L stainless steel

Certified for hazardous areas according to ATEX, IECEx, INMETEC Class Ex IP66/68 (IEC 60529)

Scratch and heat-resistant LEXAN dome for perfect optical quality in Germany

Lightfinder and WDR

Automatic temperature control

Fast pan and tilt drive (0.05 - 450°/s)

Protection Class Ex IP66/68 (IEC 60529)

Made in Germany

Specifications

Series	ExCam
Camera Type	Explosionssgeschützt
Resolution Standard	HD 1080p
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Video compression	H.264, H.265, M-JPEG
Image resolution max.	1920x1080
Image Transmission Rate	30 fps
Day&Night switch	ICR
Sensitivity	0,1 Lux bei 30 URE F1.6
Digital Noise Reduction	yes

ExCam IPQ6075 T08-TNXCD-N.H-005.N-P

Continuation of the specifications

Lens Type	auto focus zoom
Focal Length	4,25 - 170 mm
Digital Zoom	12x
Horizontal Angle of View	65 - 2°
Housing	Explosionsschutz
Color (housing)	Edelstahl
Housing material	Stainless steel
Heater	no
Video outputs	no
Alarm inputs	nein
Audio support	no
Serial interfaces	Ethernet
Internal storage	microSD-Kartenslot
Supply voltage	PoE
Power over Ethernet	IEEE 802.3at
Operating temperature	0°C ~ +60°C
ONVIF	ONVIF Profile S
Certifications	ATEX, EACex, IECEX, INMETRO, MASC, UKEX
Protection rating	IP66/68
Low Speed Shutter	yes
Backlight Compensation	n/a
Wide Dynamic Range (WDR)	120dB
Motion Detector	yes
Manufacturer order number	23040117

Optional Accessory

SKU	Name	Description
240928	Deckenmontageadapter CMB-TNXCD	Adapter for devices from the T08-VA4 and TNXCD series, also suitable for horizontal wall mounting or Pole mounting of the ExCam IPP3827
240936	ExConnection Rail T04.5-D.BOR-4PoE++-100Base	High-performance PoE switch for the Ex area IP66- and flame-resistant encapsulated housing with sight glass, Explosion protection approval 2014/34/EU
240937	ExConnection Rail T04.6-D.BOR-8PoE++-100Base	High-performance PoE switch for the Ex area IP66- and flame-resistant encapsulated housing with sight glass, Explosion protection approval 2014/34/EU
240934	ExTB-3 Klemmkasten für ExCam Serie	Model: T12-M20-M20-M20
240930	Mastadapter PMB	Mast adapter for TNXCD & T08-VA1.x/2.x wall bracke suitable for pole diameters between 100 and 150mm
240912	SKD02-T Kabel Kit 30 m	30 meter SKD02-T system cable Digital special cable with Ex approval according to DIN EN 60079-14

ExCam IPQ6075 T08-TNXCD-N.H-005.N-P

Continuation of accessory

240913	SKDP03-T Kabel Kit 30 m	30 meter SKDP03-T system cable Digital special cable with Ex approval according to DIN EN 60079-14
240917	Wandausleger WMB-TNXCD	Wall bracket for T08-TNXCD series devices Suitable for suspended mounting

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

