



# ExCam IPQ6075 T08-TNXCD-N.H-005.N-P

Continuation of the specifications

Lens Type	auto focus zoom
Focal Length	4,25 - 170 mm
Digital Zoom	12x
Horizontal Angle of View	65 - 2°
Housing	Explosionsschutz
Color (housing)	Edelstahl
Housing material	Stainless steel
Heater	no
Video outputs	no
Alarm inputs	nein
Audio support	no
Serial interfaces	Ethernet
Internal storage	microSD-Kartenslot
Supply voltage	PoE
Power over Ethernet	IEEE 802.3at
Operating temperature	0°C ~ +60°C
ONVIF	ONVIF Profile S
Certifications	ATEX, EACex, IECEx, INMETRO, MASC, UKEX
Protection rating	IP66/68
Low Speed Shutter	yes
Backlight Compensation	n/a
Wide Dynamic Range (WDR)	120dB
Motion Detector	yes
Manufacturer order number	23040117

## Optional Accessory

SKU	Name	Description
240928	Deckenmontageadapter CMB-TNXCD	Adapter for devices from the T08-VA4 and TNXCD series, also suitable for horizontal wall mounting or Pole mounting of the ExCam IPP3827
240936	ExConnection Rail T04.5-D.BOR-4PoE++-100Base	High-performance PoE switch for the Ex area IP66- and explosion-resistant encapsulated housing with sight glass, Explosion protection approval 2014/34/EU
240937	ExConnection Rail T04.6-D.BOR-8PoE++-100Base	High-performance PoE switch for the Ex area IP66- and explosion-resistant encapsulated housing with sight glass, Explosion protection approval 2014/34/EU
240934	ExTB-3 Klemmkasten für ExCam Serie	Model: T12-M20-M20-M20
240930	Mastadapter PMB	Mast adapter for TNXCD & T08-VA1.x/2.x wall bracke suitable for pole diameters between 100 and 150mm
240912	SKD02-T Kabel Kit 30 m	30 meter SKD02-T system cable Digital special cable with Ex approval according to DIN EN 60079-14

# ExCam IPQ6075 T08-TNXCD-N.H-005.N-P

Continuation of accessory

240913	SKDP03-T Kabel Kit 30 m	30 meter SKDP03-T system cable Digital special cable with Ex approval according to DIN EN 60079-14
240917	Wandausleger WMB-TNXCD	Wall bracket for T08-TNXCD series devices Suitable for suspended mounting

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

