

SKDP03-T Kabel Kit 30 m

SKU: 240913



Abb. ähnlich

30 meter SKDP03-T system cable Digital special cable with Ex approval according to DIN EN 60079-14

Main Features

| | |
|--|---|
| 30 m length | Flame retardant according to IEC 60332-1-2 |
| Meets the requirements for cables in potentially explosive atmospheres according to IEC EN 60730-1-2 and IEC EN 60730-2, 4h at 200°C | Oil resistant according to IEC EN 60730-1-2 and IEC EN 60730-2 |
| Complies with the provisions for cables in potentially explosive atmospheres in accordance with IEC EN 60730-1-2 and IEC EN 60730-2 | Multi-resistent approval zone with NEK 606 |
| Tested for -60°C to +80°C fixed installation | IEEE 802.3at PoE+, max 30 W per channel, max 95 m |
| Resistant to sunlight in accordance with UL 2556 para. 4.2.8.5 (320 h) | Designable with additional power channel: Square 3 x 1.5mm ² , c |

Specifications

| | |
|---------------------------|----------|
| Series | ExCam |
| Manufacturer order number | 26030405 |

SKDP03-T Kabel Kit 30 m

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

