

# SKDP03-T Kabel Kit 30 m

SKU: 240913



30 meter SKDP03-T system cable Digital special cable with Ex approval according to DIN EN 60079-14

Abb. ähnlich

## Main Features

30 m length

Meets the requirements for cables in potentially explosive atmosphere according to IEC EN 60079-14 and IEC EN 60079-2, 4h at 200°C

Complies with the provisions for cables in potentially explosive atmosphere according to IEC EN 60079-14 and IEC EN 60079-2, 4h at 200°C

Tested for -60°C to +80°C fixed installation

Flame retardant according to IEC 60332-1-2

Compliant according to IEC EN 60079-14 and IEC EN 60079-2, 4h at 200°C

Meets the requirements for cables in potentially explosive atmosphere according to IEC EN 60079-14 and IEC EN 60079-2, 4h at 200°C

IEEE 802.3at PoE+, max 30 W per channel, max 95 m

Resistant to sunlight in accordance with UL 2556 para. 4.2.8.5 (320 h) with additional power channel: Square 3 x 1.5mm<sup>2</sup>, c

## Specifications

Series	ExCam
Manufacturer order number	26030405

# SKDP03-T Kabel Kit 30 m

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

