

EDC-OPS-2/24V

SKU: 74136



Pendant Mount Outdoor Dome Housing with Sunshield, Tinted Bubble 6.5", 24VAC

Main Features

Outdoor housing for Fastrax I - III dome cameras

Tinted bubble 6.5" (165mm)

Prepared for wall and ceiling mounting

Sunshield, heater and blower kit included

Supply voltage: 24VAC/50-60Hz

Protection rating: IP66

Option: Wall and ceiling mount brackets, power box

Option: Connection cable #74143 & #74144

Specifications

Housing	Outdoor
Color (housing)	Pantone Cool Gray 1C
Color (bubble)	tinted
Housing material	Aluminium
Heater	yes
Mounting	Wall or ceiling pendant mount
Power consumption	approx. 75W for heater, blower and incl. dome camera
Operating temperature	-45°C ~ +50°C
Protection rating	IP66
Weight	3,6kg
Manufacturer order number	74136

EDC-OPS-2/24V

Optional Accessory

SKU	Name	Description
74125	EDC-AKS1	Power&Connection Box with Mounting Bracket for In/Outdoor, 230V-24VAC/3.0A

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

