

**VH3256**

SKU: 74326



Active 32-channel Video TP Receiver, BNC Outputs,  
19", 24VAC

**Main Features**

32-channel Twisted-pair Video Receiver	Immunity to Noise and Interference
Bandwidth: DC to 10MHz	Ground-loop and Power Surge Protection
Unshielded CAT2 (min) Cable Required	Built-in Gain and Loss Control, Video Detection
Up-to 1000m (Passive Transmitter / UTP cable)	Video, AC, Telephone, Computer Signals via 1 Cable
Up-to 2200m (Active Transmitter / TT560)	BNC Plug / Terminal Block Connectors
Cable Length Adjustment by Dip-switches	Highly Compact, One Rack Unit in Height

**Specifications**

Model	housing
Type of unit	receiver
Range	2200 m
Signal transmission	video
Protection rating	n/a
Operation mode	active
Manufacturer order number	VH3256

**Optional Accessory**

SKU	Name	Description
-----	------	-------------

# VH3256

Continuation of accessory

200537	UPA-2450-50	Netzgerät, 24VAC, 50VA, Eingang 220VAC/50Hz, für Innen
--------	-------------	--

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

