

# VH3256

SKU: 74326



Active 32-channel Video TP Receiver, BNC Outputs, 19", 24VAC

## Main Features

32-channel Twisted-pair Video Receiver

Bandwidth: DC to 10MHz

Unshielded CAT2 (min) Cable Required

Up-to 1000m (Passive Transmitter / UTP cable)

Up-to 2200m (Active Transmitter / TT560)

Cable Length Adjustment by Dip-switches

Immunity to Noise and Interference

Ground-loop and Power Surge Protection

Built-in Gain and Loss Control, Video Detection

Video, AC, Telephone, Computer Signals via 1 Cable

BNC Plug / Terminal Block Connectors

Highly Compact, One Rack Unit in Height

## Specifications

Model	housing
Type of unit	receiver
Range	2200 m
Signal transmission	video
Protection rating	n/a
Operation mode	active
Manufacturer order number	VH3256

## Optional Accessory

SKU	Name	Description
-----	------	-------------

# VH3256

Continuation of accessory

200537	UPA-2450-50	Netzgerät, 24VAC, 50VA, Eingang 220VAC/50Hz, für Innen
--------	-------------	--

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

